




SHELF & ROD SHELVING




25.4cm/ 10"
depth



30.5cm/ 12"
depth



40.6cm/ 16"
depth shelf
25.4cm/ 10"
hang



40.6cm/ 16"
depth shelf
30.5cm/ 12"
hang

GENERAL SPECIFICATIONS

Furnish and install ClosetMaid Vinyl-coated, steel rod, ventilated shelving and storage systems manufactured by ClosetMaid Corp., Florida, USA in all closets.

COATING SPECIFICATIONS

ClosetMaid heavy duty vinyl coating won't chip or split. It is a proprietary Polyvinyl Chloride Resin (PVC) with an exclusive mixture of ingredients including plasticisers, stabilisers, pigments and other additives - none of which are listed as hazardous materials.

ClosetMaid's patented plastic components are manufactured to get high performance standards and meet rigid material requirements. Nylon is specified for toughness. Hi-impact styrene is specified for rigid strength. Polypropylene is specified for consistent performance. Manufacturer reserves the right to change specifications without notice.



- All ClosetMaid wire shelving is SCS certified for a minimum of 91% recycled content
- All ClosetMaid wire shelving is SCS certified to meet Indoor Air Quality Indoor Advantage Gold requirements and supports safe and healthy indoor environments for school classroom, private office and/ or single-family residence per California Specification 01350
- All ClosetMaid wire shelving is manufactured in the USA
- If a ClosetMaid product does not give you complete satisfaction when installed in accordance with the manufacturers instructions, it will be exchanged free of charge. Please note that only the unsatisfactory part in a multi-piece product will be exchanged.

SPECIFICATIONS

- Ventilated wire shelving allows for visibility of items
- Weight must be evenly distributed across shelf
- Material: Vinyl coated steel

WIRE SHELVING PHYSICAL PROPERTIES

Materials: Grade c-1006 basic cold drawn steel wire. 13-1/2 GA and 4-1/2 GA.

Tensile Strength: Over 100,000 PSI (average)

Cross Deck Spacing: 2.54cm/ 1" increments, 13-1/2 GA

Coating: Proprietary polyvinyl chloride formula resin (PVC)

Vinyl Thickness: 9-11 mills (fluidised bed process)

Mounting Hardware: Components shall provide for shelving installation to drywall without requiring mounting to concealed wall structural members. Support brackets shall be required for 91cm/ 36" span. (61cm/ 24" recommended for areas designed for heavy use). Wall clips are required 2.5/ 1" - 5cm/ 2" from each end and every 25.4cm/ 10" - 30.5cm/ 12" in between.

INSTALLATION INSTRUCTIONS

Components provide for ClosetMaid shelving installation to drywall or plasterboard without requiring mounting to wall studs. Shelves are to be attached to walls with ClosetMaid Wall Clips, End Brackets, Support Brackets and Poles.

Shelves are to be attached to walls with ClosetMaid Wall Clips to hold back of shelf (product code #911) every 25.4cm/ 10" - 30.5cm/12" apart on level line. 0.6cm/ 0.25" holes are to be drilled with a drill bit for all wall attachment hardware. Use #8 x 2.5cm/ 1" screw. All shelves must be front supported a maximum of every 91cm/ 36" with appropriate end brackets, support brackets or poles.

Visit www.closetmaid.co.uk for complete installation instructions.

CLEANING MAINTENANCE

Clean your ClosetMaid product with a soft cloth and mild soap, rinse thoroughly with warm water, and dry with a clean, soft cloth. Never use cleaners containing abrasives.